

**Multi-parameter
monitor**
PM12B

SPO2
Optimal Parameters:

- Measuring Range: 0 ~ 100 %
- Resolution: 1%
- Accuracy: 70% ~ 100% ($\pm 2\%$)
- Pulse Rate: 20-250 BPM
- Resolution: 1 BPM
- Accuracy: ± 3 BPM

- Recorder (Printer)
- Central monitoring system
- Dual IBP
- EtcO2
- 12-lead ECG;
- Nellcor SpO2;
- Sun Tech NIBP.

NIBP
TEMP
Standard Configuration:

- Method: Oscillometry
- Measure mode: Manual, Auto, STAT
- Unit: mmHg, kPa
- Measure and alarm range:

- Adult Mode
 - SYS 40 ~ 280 mmHg
 - DIA 10 ~ 225 mmHg
 - MEAN 20 ~ 240 mmHg

- Pediatric Mode
 - SYS 40 ~ 220 mmHg
 - DIA 10 ~ 160 mmHg
 - MEAN 20 ~ 170 mmHg

- Neonatal Mode
 - SYS 40 ~ 135 mmHg
 - DIA 10 ~ 100 mmHg
 - MEAN 20 ~ 110 mmHg
- Resolution: 1mmHg
- Accuracy: ± 5 mmHg

- Measure and Alarm Range: 0 ~ 50 C
- Resolution: 0.1C
- Accuracy: ± 0.1 C

Standard Parameters:

- ECG, RESP, TEMP, NIBP, SPO2, PR

RESP

- Method: Impedance between RA-LL or RALA
- Measurement Range:
 - Adult: 10 ~ 120 BrPM
 - Neonatal / Pediatric: 7 ~ 150 BrPM
- Resolution: 1 BrPM
- Accuracy: ± 2 BrPM

No.	Item	Qty
1	Main Unit	1
2	5-lead ECG cable	1
3	Disposable ECG Electrode	5
4	Adult Spo2 probe	1
5	Adult NIBP cuff	1
6	NIBP extension tube	1
7	Temperature probe	1
8	Power Cable	1
9	User Manual	1
10	Fuse	3

Packing:

- Single package size: 37*28*36cm
- Single gross weight: 4.5 KG
- 4 unit per carton, package size: 58*39*75cm, total gross weight 20 KG